



HA5-Plus

Bring HDMI and 3G-SDI devices together for a full range of monitoring and recording solutions in the edit suite, on set or at live events. Convenient USB setup using AJA MiniConfig on Mac or PC for easy remote configuration.

\$525 US MSRP

<https://www.aja.com/products/ha5-plus>

Video Formats

- (HD) 1920x1080p
- (HD) 1920x1080i
- (HD) 1280x720p
- (SD) 720x576p
- (SD) 720x576i
- (SD) 720x480p
- (SD) 720x480i

Note: HDCP content not supported

Video Input Digital

- 1x HDMI Type A connector, HDMI v1.4
- YCbCr 4:2:2/4:4:4/4:2:0
- 8 or 10-bit (HFR 4:2:2 limited to 10-bit)
- (HD) 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- (HD) 1920x1080i 50, 59.94, 60
- (HD) 1280x720p 50, 59.94, 60
- (SD) 720x576p 50
- (SD) 720x576i 25
- (SD) 720x480p 59.94
- (SD) 720x480i 29.97

Video Output Digital

- 1x 3 Gb SDI (Level A or B Dual Link)
 - (HD) 1920x1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - (HD) 1920x1080i 50, 59.94, 60
 - (HD) 1280x720p 50, 59.94, 60
- 1x 1.5 Gb SDI
 - (HD) 1920x1080p 23.98, 24, 25, 29.97, 30
 - (HD) 1920x1080i 50, 59.94, 60
 - (HD) 1280x720p 50, 59.94, 60
- 1x 270 Mb SDI
 - (SD) 625i 50
 - (SD) 525i 59.94

Audio Input Digital

- HDMI embedded audio, 24-bit, 8-channel
- 2-Channel RCA style analog audio (-10 dBu nominal)

Audio Output Digital

- SDI embedded audio, 24-bit, 8-channel

Size (w x d x h)

- 4.6" x 2.4" x 1.0" (116.84 x 60.96 x 25.4 mm)

Weight

- 0.3 lb (0.2 kg)

Power

- Universal power supply included
- 100-240V, 50/60 Hz universal input
- +5V DC regulated, 7.5 watt capacity

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)